

Energizer_• Solar

EV Chargers Three Phase Residential

Energizer

The Energizer Solar EV charger adopts a streamlined and simple design, which is more refined and technology advanced. Through the App, the car owner can choose the Bluetooth smart lock, timing charging function, or modify it to plug and play mode. At the same time, it can monitor charging information, set EV charger parameters, bind equipment and authorization, and upgrade remote software.

- Power: 11kW
- Output Current: Max.16A
- Output Voltage: 400V AC
- Type 2 cable charging connector
- Compliant with OCPP 1.6 (JSON)/2.0
- App operation or RFID authentication or plug, play & 4G
- Protection Grade: IP55
- -30 ~ 50°C wide Operating Temperature
- 3 Year Warranty

hello@energizersolar.com () energizersolar.com



Intelligent

Control

Flexible

Options

Secure

& Safe

11kW

© 2024 Energizer. Energizer and certain graphic designs are trademarks of Energizer Brands, LLC and related subsidiaries and are used under license by 8 Star Energy Pty Ltd. All other brand names are trademarks of their respective owners. Neither 8 Star Energy Pty Ltd nor Energizer Brands is affiliated with the respective owners of their trademarks.

Energy

Savings



MODEL TYPE	A11-CP Charging Plug	A11-CS Charging Socket	
INPUT			
Wiring Scheme		3P+N+PE	
Voltage		400VAC, ±20%	
Maximum Current	16A		
Frequency	50/60)Hz	
ОИТРИТ			
Voltage	400VAC,	400VAC, ±20%	
Maximum Current	16A		
Rated Power	11kV	11kW	
USER INTERFACE			
Connector Type	Type 2 Cable	Type 2 Socket (with shutter)	
RFID Reader	Mifare ISO/IEC 14443 A		
Start Mode	Plug&Play/RFI	Plug&Play/RFID card/App	
COMMUNICATION			
Wi-Fi, Bluetooth	YES		
4G, Ethernet	Optional		
ОСРР	OCPP 1.6 JSON, OC	OCPP 1.6 JSON, OCPP 2.0 optional	
SAFETY			
IP Protection Rating	IP55		
IK Protection Rating	IK08		
Residual Current Detection	AC 30mA/DC 6mA		
Over current protection	YES		
Residual current protection	YES		
Ground protection	YES		
Surge protection	YES		
Over/Under voltage protection	YES		
Over/Under frequency protection	YES		
Over/Under temperature protection	YES		
EMC	Class B		
Certification		CE	
Certification Standard	EN/IEC 61851-1: 2019, EN	EN/IEC 61851-1: 2019, EN/IEC 61851-21-2: 2021	
OTHER SPECIFICATION			
Installation		Wall-mount / Post-mount	
Operating Temperature	-30°C ~ 50°C		
Operating Humidity	5% ~ 95% (no condensation)		
Operating Altitude		<2000m	
Product Dimensions (H x W X D)	320 x 190 x 130mm	320 x 190 x 144.5mm	
Product Weight	3.55kg	2.0kg	
Country of Manufacturer	China		
Warranty	3 Yea	3 Years	