

The Energizer Solar EV charger adopts a streamlined and simple design, which is more refined and technology advanced. Through the App, the car owner can choose the Bluetooth smart lock, timing charging function, or modify it to plug and play mode. At the same time, it can monitor charging information, set EV charger parameters, bind equipment and authorization,

and upgrade remote software.

Power: 7.3kW

Output Current: Max.32A

Output Voltage: 230V AC

Type 2 cable charging connector

Compliant with OCPP 1.6 (JSON)/2.0

App operation or RFID authentication or plug, play & 4G

Protection Grade: IP55

-30 ~ 50°C wide Operating Temperature

3 Year Warranty















| MODEL TYPE | A7-CP Charging Plug | A7-CS Charging Socket |
|-----------------------------------|--|------------------------------|
| INPUT | | |
| Wiring Scheme | 1P+N+PE | |
| Voltage | 230VAC, ±20% | |
| Maximum Current | 32A | |
| Frequency | 50/60Hz | |
| ОИТРИТ | | |
| Voltage | 230VAC, ±20% | |
| Maximum Current | 32A | |
| Rated Power | 7.3kW | |
| USER INTERFACE | | |
| Connector Type | Type 2 Cable | Type 2 Socket (with shutter) |
| RFID Reader | Mifare ISO/IEC 14443 A | |
| Start Mode | Plug&Play/RFID card/App | |
| COMMUNICATION | | |
| Wi-Fi, Bluetooth | YES | |
| 4G | Optional (coming soon) | |
| OCPP | OCPP 1.6 JSON, OCPP 2.0 optional (coming soon) | |
| SAFETY | | |
| IP Protection Rating | IP55 | |
| IK Protection Rating | IK08 | |
| Residual Current Detection | AC 30mA/DC 6mA | |
| Over current protection | YES | |
| Residual current protection | YES | |
| Ground protection | YES | |
| Surge protection | YES | |
| Over/Under voltage protection | YES | |
| Over/Under frequency protection | YES | |
| Over/Under temperature protection | YES | |
| EMC | Class B | |
| Certification | CE | |
| Certification Standard | EN/IEC 61851-1: 2019, EN | /IEC 61851-21-2: 2021 |
| OTHER SPECIFICATION | | |
| Installation | Wall-mount / Post-mount | |
| Operating Temperature | -30°C ~ 50°C | |
| Operating Humidity | 5% ~ 95% (no condensation) | |
| Operating Altitude | <2000m | |
| Product Dimensions (H x W X D) | 320 x 190 x 130mm | 320 x 190 x 144.5mm |
| Product Weight | 3.55kg | 2.0kg |
| Country of Manufacturer | China | |
| Warranty | 3 Years | |